

LED HIGHBAY SMD 0002 TYPE B SERIES



SPECIFICATION

| | |
|-------------------------|--------------|
| Input Voltage (V) | AC220V |
| Power Frequency (Hz) | 50-60Hz |
| Material | Aluminum |
| LED type | SMD |
| Luminaire efficacy | 120 lm/W |
| Ambient Temp.(°C) | -20°C ~ 40°C |
| Beam Angle | 120° |
| Power Factor | > 0.6 |
| IP Rating | IP54 |
| Life time (Hrs.) | 30,000 Hrs. |
| LED Falling Down Safety | 10m. |



STANDARD

TIS.1955-2551 Lighting and Similar Equipment : Radio Disturbance limits



| Product Model | Power | CCT | Lumen(Lm) | Dimension(MM) | REMARK |
|---------------------|-------|-------------|-----------|---------------|--------|
| HB0002-50W-(30/65) | 50W | 3000K/6500K | 6,000lm | Ø340xH220 | |
| HB0002-100W-(30/65) | 100W | 3000K/6500K | 12,000lm | Ø430xH240 | |
| HB0002-150W-(30/65) | 150W | 3000K/6500K | 18,000lm | Ø430xH240 | |
| HB0002-200W-(30/65) | 200W | 3000K/6500K | 24,000lm | Ø500xH290 | |
| HB0002-250W-(30/65) | 250W | 3000K/6500K | 30,000lm | Ø500xH330 | |
| HB0002-300W-(30/65) | 300W | 3000K/6500K | 36,000lm | Ø500xH370 | |